

TELEMETRY DISPLAY T24-HS



Single Channel Hand Held Radio Telemetry Transceiver & Display

This wireless handheld display module provides an 8 digit LCD reading from any of the T24 Acquisition Modules (strain gauge, current, voltage, temperature, pulse and potentiometer).

The remote acquisition module can be 'powered on' and 'powered off' automatically as the T24-HS handheld is operated. Status indicators inform the user if the remote acquisition module has input integrity problems, low battery, low signal, over range or other error.

The licence free 2.4GHz direct sequence spread spectrum (DSSS) radio telemetry technology offers high integrity, error free communications which can co-exist with other wireless technologies such as Wi-Fi, Bluetooth® and Zigbee®. FCC, ETSI and IC approvals.



Overview of T24 Range



FEATURES :

- Radio telemetry handheld display for connection of one T24 remote Acquisition Module
- Two key operation offers tare functionality
- Auto 'power on' and 'power off' of remote acquisition module
- Water-proofed to IP65 NEMA 4
- Simple wireless configuration and calibration
- Up to 200m (650 ft) range



PT APMS INDONESIA

Puri Industrial Park 2000
Blok E No. 1E
Batam - Indonesia

Phone : (0778) 7494 885
Email : sales_id@apms.asia
Website : apms.asia